


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	15-0016	MADE SEPARATE DRAWING FOR THIS TOOL FROM KIT RBW109-3130-84-101.	1/19/2015	RJC	JAG
2	16-0103	UPDATED TO NEW STANDARD. -1 CH'D DIMS WAS (.625) IS .63, WAS 10X .09 X 45° IS 8X .09 X 45°. ADDED DIM 2X .09 X 45°.	8/11/2016	DEW	SM





NOTE:
1. REF. AGUSTA T/N: 109-3130-84-109.
2. PART OF KIT RBW109-3130-84-101.

DART AEROSPACE	
TITLE REACTOR TOOL	
DWG NO. RBW109-3130-84-109	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125°
TREAT ANODIZE	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
FINISH AS PLATED	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
SPEC ASME Y14.5M-2009	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DRAWN BY: CLOUGH	USED ON MODEL AW119
CHECKED: DUERFELDT	
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: MACKOVJAK	
SCALE 1:4	DATE 1/19/2015
SHEET 1 OF 2	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	REACTOR TOOL	6061		2
		B/O	-3	3	SOCKET HEAD CAP SCREW	STEEL	M6 X 1 X 16mm (MCMASTER-CARR #95263A531)	1
		B/O	-5	3	WASHER	STEEL	M6 (MCMASTER-CARR #91455A120)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0103	-1 CH'D DIMS WAS (.625) IS .63, WAS 10X .09 X 45° IS 8X .09 X 45°. ADDED DIM 2X .09 X 45°.	8/11/2016	DEW	SM



(-1)
REACTOR TOOL

DART AEROSPACE	
TITLE REACTOR TOOL	
DWG NO. RBW109-3130-84-109-1	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8
FINISH CLEAR ANODIZE	.XX ± .01 ANGLES ± .5°
SPEC MIL-A-8625F, TYPE II, CLASS I	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: MACKOVJAK	AW119
SCALE 1:4	DATE 1/19/2015
SHEET 2 OF 2	